

TUTORS:

Yaser Jaradeh, Hassan Hussien, and some other ORKG members

QUESTIONS: Please don't hesitate to ask any questions. Questions help you and your peers.

PRINT: Please consider the environment before printing the exercise.

1 NNF Rules

$$\begin{aligned}
 A \Rightarrow B &\rightarrow \neg A \vee B \\
 A \Leftrightarrow B &\rightarrow (\neg A \vee B) \wedge (A \vee \neg B) \\
 \neg(A \vee B) &\rightarrow \neg A \wedge \neg B \\
 \neg(A \wedge B) &\rightarrow \neg A \vee \neg B \\
 \neg\neg A &\rightarrow A \\
 \neg\exists x A &\rightarrow \forall x \neg A \\
 \neg\forall x A &\rightarrow \exists x \neg A
 \end{aligned}$$

2 ALC to NNF

Convert the following ALC axioms into Negation Normal Form (NNF)

- $\neg(A \vee \neg B)$
Solution:
 $NNF(\neg(A \vee \neg B))$
 $= NNF(\neg A) \wedge NNF(\neg\neg B)$
 $= NNF(\neg A) \wedge NNF(B)$
 $= \neg A \wedge B$
- $\neg(\neg(A \vee \neg B) \wedge \neg C)$
Solution:
 $NNF(\neg(\neg(A \vee \neg B) \wedge \neg C))$
 $= NNF(\neg\neg(A \vee \neg B) \vee NNF(\neg\neg C))$
 $= NNF(A \vee \neg B) \vee NNF(C)$
 $= NNF(A \vee \neg B) \vee C$
 $= NNF(A) \vee NNF(\neg B) \vee C$
 $= A \vee \neg B \vee C$
- $\neg(A \Rightarrow B) \vee (C \Rightarrow D)$
Solution:
 $NNF(\neg(A \Rightarrow B) \vee (C \Rightarrow D))$
 $= NNF(\neg(\neg A \vee B) \vee (\neg C \vee D))$
 $= NNF(\neg(\neg A \vee B)) \vee NNF(\neg C \vee D)$
 $= NNF(\neg\neg A \wedge \neg B) \vee NNF(\neg C \vee D)$
 $= NNF(\neg\neg A) \wedge NNF(\neg B) \vee NNF(\neg C) \vee NNF(D)$
 $= NNF(A) \wedge NNF(\neg B) \vee NNF(\neg C) \vee NNF(D)$
 $= A \wedge \neg B \vee \neg C \vee D$
- $\neg(\forall r. A \vee B)$
Solution:
 $NNF(\neg(\forall r. A \vee B))$
 $= \exists r. NNF(\neg(A \vee B))$

$$\begin{aligned}
&= \exists r. NNF(\neg A \wedge \neg B) \\
&= \exists r. NNF(\neg A) \wedge NNF(\neg B) \\
&= \exists r. \neg A \wedge \neg B
\end{aligned}$$

3 SHACL Shapes

Consider the following SHACL shapes graph:

```

@prefix ex: <http://example.org/> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix sh: <http://www.w3.org/ns/shacl#> .

```

```

ex:PersonShape
  a sh:NodeShape ;
  sh:targetClass ex:Person ;
  sh:property [
    sh:path ex:name ;
    sh:datatype xsd:string ;
    sh:minLength 3 ;
    sh:maxLength 20 ;
  ] .

```

Based on the provided SHACL shapes graph, write an RDF data graph that conforms to the defined constraints.

Solution:

```

@prefix ex: <http://example.org/> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .

```

```

ex:Harry a ex:Person ; ex:name "Harry" .

```

```

ex:Ron a ex:Person ; ex:name "Ronald Weasley" .

```